

The 1680 track is a compact, highly maneuverable grinder. Featuring an 18" high x 52" wide mill opening, this unit has ample room to efficiently process brush, logs, and other wood waste. The large diameter mill with 26 teeth is designed for maximum cutting efficiency utilizing less horsepower and fuel.

# PRODUCE MORE. PAY

The Beast's patented cuttermill utilizes a unique cutterbody holder that regulates the size of the cut. The result is a more uniform product using less energy to process material. This results in savings in fuel, wear and tear, and most importantly - time - because you get the right size on the first pass.

The Model 1680XP is built to stand up to any daily grind. Solid steel welded construction and the industry's best components combine to create a machine professionals can trust to perform. And when you need parts or service, turn to our worldwide network of authorized dealers who are ready to offer their support.



6750 Millbrook Rd. • Remus, MI 49340 • 1-800-952-0178









Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments

## SPECIFICATIONS

MEASUREMENTS		1680XP TRACK
Length:	26'7"	810.3 cm
Width:	8' 3"	251.5 cm
Height:	12' 6"	381 cm
Weight:	37,580 lbs. (17,046 kg)	
Engines:	300-321 HP (224-239kW)	
Fuel Tank:	100 gal.	379 L
Hydraulic Tank:	80 gal.	303 L

ENGINE OPTION 1	ENGINE OPTION 2	
Make and Model: CAT C7.1	Make and Model: John Deere 6.8	
Gross HP: 321 HP (239.4 kW)	Gross HP: 300 HP (223.71 kW)	
Fan: Reversing	Fan: Reversing	
Clutch Type: Fluid	Clutch Type: Fluid	

DIMENSIONS			
Capacity:	18" Capacity	45.7 cm Capacity	
Opening:	18" tall x 52" wide	45.7 cm x 132 cm wide	
Cuttermill:	36" dia. x 52" wide	91 cm dia. x 132 cm wide	
Teeth:	26		
Feed Wheel:	(1) 16" dia. x 50.75" wide	(1) 40.6 cm x 129 cm wide	
Infeed Conveyor: Single speed, 8'10" long x 52" wide			

Infeed Conveyor: Single speed, 8'10" long x 52" wide (269.24 cm long x 132 cm wide)

Discharge Conveyor: 26' 5" long x 48" wide (805.2 cm long x 121.9 cm wide), up to 375 feet per minute (114.3 m/minute) conveyor speed, stacking height 14'5" ( 439.42 cm)

### **UNDERCARRIAGE AND TRACK OPTIONS**

Track: 312B Steel tracks equipped with Caterpillar track undercarriage and triple grouser shoes. 3.3MPH (5.3 km/h), 14.5" (37 cm)

### **Standard & Custom Colors Available**

Choose from two standard colors, or select a custom color to match your fleet.





Bandit Yellow

Since 1983, Bandit has manufactured equipment for a multitude of wood waste processing markets. The vision since the beginning, is to build quality, highly productive, easy to maintain equipment providing years of dependable service.

The commitment for quality, innovation and dedication is instilled in every employee and is one of the main reasons why Bandit became an Employee-Owned Company (ESOP) in 2018. These core values ensure each Bandit machine will leave the factory ready to exceed your expectations.

Caterpillar 312B steel track undercarriage can be added to the 1680XP. This feature allows it to travel over rough terrain not accessible by towable units. It also eliminates the need to forward or skid material to the grinder - the operator can take the grinder to the trees.



When you choose a Bandit, you'll experience more uniform end product production, smoother and more efficient grinder, long-lasting components and improved fuel economy. We invite you to see for yourself by scheduling a demo with your nearest authorized Bandit dealer.



**Bandit Offers a Complete Line of Tree Care Equipment:** Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast® Horizontal Grinders • Track Carriers • Attachments